

SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier	
Trade name or designation of the mixture	JURID Brake Fluid
Registration number	
Synonyms	DOT 5.1 - All grades, DOT 4 - grades with Wet Boiling Points > 165 °C.
Product code	151042J, 151092J, 151095J, 151744J, 151794J
Issue date	13-May-2024
Version number	01
Revision date	-
Supersedes date	-
1.2. Relevant identified uses of	the substance or mixture and uses advised against
Identified uses	Hydraulic fluid in automotive brake/clutch system.
Uses advised against	None known.
1.3. Details of the supplier of the	e safety data sheet
Manufacturer/Supplier	
Company name	Federal-Mogul Global Aftermarket EMEA bv
Address	Prins Boudewijnlaan 5
	B-2550 Kontich
	Belgium
Telephone	+32 3 450 83 10
Contact person	Braking_EMEA@DRiV.com
1.4. Emergency telephone number	3E Global Incident Response Hotline
	+44 20 35147487
	Access code: 335908
General emergency	112 or 999 SDS/Product information may not be available for the Emergency
	Service.
Non-emergency medical helpline	111 SDS/Product information may not be available for the Emergency Service.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended

Health hazards


Reproductive toxicity (fertility, the unborn child)	Category 2	H361fd - Suspected of damaging fertility. Suspected of damaging the
		unborn child.


2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

Contains:

Tris[2-[2-(2-methoxyethoxy) ethoxy]ethyl] orthoborate







Signal word

Warning

Hazard statements H361fd

Suspected of damaging fertility. Suspected of damaging the unborn child.

Precautionary statements	
Prevention	······
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
Response	
P308 + P313	IF exposed or concerned: Get medical advice/attention.
Storage	
P405	Store locked up.
Disposal	
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
Supplemental information on the label	None.
2.3. Other hazards	This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Tris[2-[2-(2-methoxyethoxy) ethoxy]ethyl] orthoborate	80 - 95	30989-05-0 250-418-4	01-2119462824-33-XXXX	-	
Classification	Repr. 2;H3	361fd			
Triethylene glycol monobutyl ether	10 - 15	143-22-6 205-592-6	01-2119475107-38-XXXX	603-183-00-0	
Classification	Eye Dam.	1;H318			
3,6,9,12-Tetraoxahexadecan-1-ol	1 - 3	1559-34-8 216-322-1	01-2120768763-41-XXXX	-	
Classification	Eye Irrit. 2	;H319			
2-(2-Methoxyethoxy)ethanol	< 1	111-77-3 203-906-6	01-2119475100-52-XXXX	603-107-00-6	#
Classification	Repr. 1B;H	1360D			

List of abbreviations and symbols that may be used above

#: This substance has been assigned Community workplace exposure limit(s).

Composition comments All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume. The full text for all H-statements is displayed in section 16.

SECTION 4: First aid measures

General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. IF exposed or concerned: Get medical advice/attention.
4.1. Description of first aid meas	sures
Inhalation	Move injured person into fresh air and keep person calm under observation. Get medical attention if any discomfort continues.
Skin contact	Remove contaminated clothes and rinse skin thoroughly with water. Get medical attention if irritation develops and persists.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Ingestion	Rinse mouth thoroughly with water and give large amounts of milk or water, if person is conscious. Get medical attention if any discomfort continues.
4.2. Most important symptoms and effects, both acute and delayed	Exposed individuals may experience eye tearing, redness, and discomfort. Defats the skin. Central nervous system. Headaches, dizziness and nausea. May cause abdominal discomfort if swallowed.
4.3. Indication of any immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Symptoms may be delayed.

SECTION 5: Firefighting measures

General fire hazards Will burn if involved in a fire.

5.1. Extinguishing media	
Suitable extinguishing media	Alcohol resistant foam. Dry powder. Carbon dioxide (CO2). Water mist.
Unsuitable extinguishing media	Water jet.
5.2. Special hazards arising from the substance or mixture	During fire, gases hazardous to health may be formed.
5.3. Advice for firefighters	
Special protective equipment for firefighters	Self-contained breathing apparatus and full protective clothing should be worn when fighting chemical fires. Selection of respiratory protection for firefighting: follow the general fire precautions indicated in the workplace.
Special fire fighting procedures	Use standard firefighting procedures and consider the hazards of other involved materials. Containers close to fire should be removed immediately or cooled with water.

SECTION 6: Accidental release measures

	6.1. Personal precautions, protect	ctive equipment and emergency procedures
	For non-emergency personnel	Follow standard emergency procedure. Avoid breathing mist/vapours. Wear appropriate personal protective equipment (See Section 8).
	For emergency responders	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Avoid contact with skin and eyes. Ensure adequate ventilation. Wear appropriate protective equipment and clothing during clean-up. Local authorities should be advised if significant spillages cannot be contained. Use personal protection recommended in Section 8 of the SDS.
	6.2. Environmental precautions	Avoid discharge into drains, water courses or onto the ground.
		Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.
		Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
		Never return spills to original containers for re-use.
	6.4. Reference to other sections	For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.
	SECTION 7: Handling and	storage
	7.1. Precautions for safe	Obtain special instructions before use. Do not handle until all safety precautions have been read

7.1. Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing mist/vapours. Avoid contact with skin and eyes. Avoid prolonged exposure. Pregnant or breastfeeding women must not handle this product. Provide adequate ventilation. Wear appropriate personal protective equipment. For personal protection, see Section 8 of the SDS. Observe good industrial hygiene practices.
7.2. Conditions for safe storage, including any incompatibilities	Store locked up. Keep container in a well-ventilated place. Store between 15°C - 30°C (60°F - 86°F). Store away from incompatible materials (see section 10 of the SDS).
7.3. Specific end use(s)	Hydraulic fluid in automotive brake/clutch system.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

UK. OELs. Workplace Exposure Limits (WELs) (EH40/2005 (Fourth Edition 2020)), Table 1 Components Type Value

Components	Туре	Value	
2-(2-Methoxyethoxy)ethanol (CAS 111-77-3)	TWA	50.1 mg/m3	
		10 ppm	
Biological limit values	No biological exposure limits noted for the	ingredient(s).	
Recommended monitoring procedures	Follow standard monitoring procedures.		
Derived no effect levels (DNELs)			

General population

Components	Value	Assessment factor	Notes
2-(2-Methoxyethoxy)ethanol (CAS 111-77-3)			
Long-term, Systemic, Dermal	1.33 mg/kg bw/day	30	Repeated dose toxicity
Long-term, Systemic, Inhalation	30.1 mg/m3		
Long-term, Systemic, Oral	7.5 mg/kg bw/day	120	Repeated dose toxicity

3,6,9,12-Tetraoxahexadecan-1-	ol (CAS 1559-31-8)		
Long-term, Systemic, Oral	3 mg/kg bw/da	v 200	Repeated dose toxicity
Triethylene glycol monobutyl et	00	y 200	Repeated dose toxicity
Long-term, Systemic, Dern	, ,	40	Papastad dasa taxisity
Long-term, Systemic, Inhal		40	Repeated dose toxicity Repeated dose toxicity
Long-term, Systemic, Oral	12.5 mg/kg/da		Repeated dose toxicity
Tris[2-[2-(2-methoxyethoxy) eth			
Long-term, Systemic, Dern		100	Repeated dose toxicity
Long-term, Systemic, Den	10 mg/kg	100	Repeated dose toxicity
<u>Workers</u>			
Components	Value	Assessment fac	tor Notes
2-(2-Methoxyethoxy)ethanol (C	AS 111-77-3)		
Long-term, Systemic, Dern Long-term, Systemic, Inhal		/day 18	Repeated dose toxicity
Triethylene glycol monobutyl et	•		
Long-term, Systemic, Dern	()	24	Repeated dose toxicity
Long-term, Systemic, Inhal		6	Repeated dose toxicity
•	0		Repeated dose toxicity
Tris[2-[2-(2-methoxyethoxy) eth			B () () () ()
Long-term, Systemic, Dern		60	Repeated dose toxicity
dicted no effect concentration	s (PNECs)		
Components	Value	Assessment fac	tor Notes
2-(2-Methoxyethoxy)ethanol (C	AS 111-77-3)		
Freshwater	12 mg/l	100	
Intermittent releases	12 mg/l		
Marine water	1.2 mg/l	1000	
Secondary poisoning	0.09 g/kg	200	Oral
Sediment (freshwater)	44.4 mg/kg		
Sediment (marine water) Soil	0.44 mg/kg 2.1 mg/kg		
STP	10000 mg/l	1	
3,6,9,12-Tetraoxahexadecan-1-	-	·	
Freshwater		1000	
Marine water	2.5 mg/l 0.25 mg/l	1000 1000	
Sediment (freshwater)	9.49 mg/kg	1808	
Sediment (marine water)	0.9 mg/kg		
Soil	0.46 mg/kg		
Triethylene glycol monobutyl et			
Freshwater	2 mg/l	50	
Intermittent releases	8.4 mg/l	00	
Marine water	0.2 mg/l	500	
Secondary poisoning	111 mg/kg	90	Oral
Sediment (freshwater)	7.7 mg/kg		
Sediment (marine water)	0.77 mg/kg		
Soil	0.47 mg/kg		
STP	200 mg/l	10	
Tris[2-[2-(2-methoxyethoxy) eth		,	
Freshwater	0.211 mg/l	1000	
Intermittent releases	2.112 mg/l		
Marine water	0.021 mg/l	10000	
Sediment (freshwater)	0.76 mg/kg		
Sediment (marine water) Soil	0.076 mg/kg 0.028 mg/kg		
STP	100 mg/l	10	
oosure guidelines			
	ion		
UK EH40 WEL: Skin designat			l sin
2-(2-Methoxyethoxy)ethan	DI (CAS 111-77-3)	Can be absorbed through the s	skin.
. Exposure controls			
	applicable, use process enclos maintain airborne levels below		

In

Individual protection measures,	such as personal protective equipment
General information	Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.
Eye/face protection	Wear safety glasses with side shields (or goggles). Eye protection should meet standard EN 166.
Skin protection	
- Hand protection	Wear appropriate chemical resistant gloves. Full contact: Glove material: Butyl rubber. Use gloves with breakthrough time of >480 minutes minutes. Minimum glove thickness 0.3 mm. Nitrile. Use gloves with breakthrough time of > 480 minutes. Minimum glove thickness 0.2 mm. Always wear chemical-resistant protective gloves that comply with EN 374 to handle this product. Observe good industrial hygiene practices and wash gloves with soap and water before removing them. Assess the working conditions and always consult your glove supplier for information on the most suitable type of glove for each task and the required material, thickness, and breakthrough time specifications. The use of type-B gloves in accordance with EN 374 is recommended as a minimum protection against intermittent or splash contact. Consult your supplier to find the most suitable option for the product in question. The requirements of EN 388 must be taken into account for applications involving mechanical hazards with the risk of abrasion or incision. The requirements outlined in EN 407 must be taken into consideration for tasks involving thermal hazards.
- Other	Wear appropriate clothing to prevent repeated or prolonged skin contact.
Respiratory protection	In case of inadequate ventilation or when the product is heated, use suitable respiratory equipment with gas filter (type A2). Respiratory protection should meet standard EN 14387. Appropriate respirator selection should be made by a qualified professional.
Thermal hazards	When material is heated, wear gloves to protect against thermal burns.
Hygiene measures	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Observe any medical surveillance requirements.
Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. Fume scrubbers, filters or engineering modifications to the process equipment may be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	
Physical state	Liquid.
Form	Liquid.
Colour	Amber.
Odour	Mild.
Odour threshold	Not available.
рН	7 - 10.5
Melting point/freezing point	< -50 °C (< -58 °F)
Initial boiling point and boiling range	> 260 °C (> 500 °F)
Flash point	> 120 °C (> 248 °F)
Evaporation rate	0.01 (n-butylacetate = 100)
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or exp	losive limits
Explosive limit - lower (%)	Property has not been measured.
Explosive limit – upper (%)	Property has not been measured.
Vapour pressure	1 mbar
Vapour density	Property has not been measured.
Relative density	1.02 - 1.07
Solubility(ies)	
Solubility (water)	Soluble in water.
Partition coefficient (n-octanol/water)	1.5
Auto-ignition temperature	> 280 °C (> 536 °F)
Decomposition temperature	300 °C (572 °F)
Viscosity	Property has not been measured.

Explosive properties	Not explosive.
Oxidising properties	Not oxidising.
9.2. Other information	
Kinematic viscosity	5 - 10 cSt (20 °C (68 °F))

SECTION 10: Stability and reactivity

10.1. Reactivity	The product is stable and non reactive under normal conditions of use, storage and transport.
10.2. Chemical stability	Stable under normal temperature conditions. Glycol Ethers can form peroxides on storage – do not distil to dryness.
10.3. Possibility of hazardous reactions	Will not occur.
10.4. Conditions to avoid	Avoid exposure to high temperatures or direct sunlight. Contact with incompatible materials.
10.5. Incompatible materials	Strong oxidizers, strong acids, and strong bases. Strong reducing agents.
10.6. Hazardous decomposition products	Fire or high temperatures create: Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

Occupational exposure to the substance or mixture may cause adverse effects.
xposure
Glycol does not easily form a vapour at normal temperatures. Therefore, it must be heated or misted before inhalation exposure can occur.
Prolonged or repeated contact may dry skin and cause dermatitis.
Based on available data, the classification criteria are not met.
May cause discomfort if swallowed.
Exposed individuals may experience eye tearing, redness, and discomfort. Defats the skin. Central nervous system. Headaches, dizziness and nausea. May cause abdominal discomfort if swallowed.

11.1. Information on toxicological effects

Acute tox	KICITY

Product	Species	Test Results	
JURID Brake Fluid (CAS Mixtu	re)		
<u>Acute</u>			
Dermal			
LD50	Rabbit	> 3000 mg/kg	
Oral			
LD50	Rat	> 5000 mg/kg	
Components	Species	Test Results	
2-(2-Methoxyethoxy)ethanol (C	AS 111-77-3)		
<u>Acute</u>			
Dermal			
LD50	Rabbit	8980 ml/kg	
Oral			
LD50	Rat	6700 ml/kg	
Triethylene glycol monobutyl e	ther (CAS 143-22-6)		
<u>Acute</u>			
Dermal			
LD50	Rabbit	3540 mg/kg	
Oral			
LD50	Rat	5300 mg/kg	
Skin corrosion/irritation	Based on available data, the classification criteria are not met.		
Serious eye damage/eye irritation	Based on available data, the classification criteria are not met.		
Respiratory sensitisation	Based on available data, the classification criteria are not met.		
Skin sensitisation	Based on available data, the classification criteria are not met.		
Germ cell mutagenicity	Based on available data, the classification criteria are not met.		
Carcinogenicity	Based on available data, the classification criteria are not met.		

Reproductive toxicity	Suspected of damaging fertility. Suspected of damaging the unborn child.			
Specific target organ toxicity - single exposure	Based on	Based on available data, the classification criteria are not met.		
Specific target organ toxicity - repeated exposure	Due to par	Due to partial or complete lack of data the classification is not possible.		
Aspiration hazard	Based on	available data, the classification crite	eria are not met.	
Mixture versus substance information	No informa	No information available.		
Other information		Glycol ethers: Some glycol ethers cause adverse effects in animals that include the reproductive system, offspring, blood, kidney and liver.		
SECTION 12: Ecological in	nformatio	n		
12.1. Toxicity	Based on environme		eria are not met for hazardous to the aquatic	
Components		Species	Test Results	
Triethylene glycol monobutyl ether Aquatic Acute	r (CAS 143-2	22-6)		
	LC50	Pimephales promelas	2400 mg/l, 96 hours	
12.2. Persistence and degradability	Expected	to be inherently biodegradable. Expe	ected to be readily biodegradable. (OECD 302B).	
12.3. Bioaccumulative potential	The produ	ct is not expected to bioaccumulate.		
Partition coefficient n-octanol/water (log Kow) JURID Brake Fluid 2-(2-Methoxyethoxy)ethanol (Triethylene glycol monobuty)				
Bioconcentration factor (BCF)	Not availa	ble.		
12.4. Mobility in soil	This produ	uct is water soluble and may disperse	e in soil.	
12.5. Results of PBT and vPvB assessment	This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.			
12.6. Other adverse effects	None know	wn.		
SECTION 13: Disposal co	nsideratio	ons		
13.1. Waste treatment methods				
Residual waste		ntainers or liners may retain some pro ed of in a safe manner (see: Disposa	oduct residues. This material and its container must I instructions).	
Contaminated packaging			esidue, follow label warnings even after container is an approved waste handling site for recycling or	
EU waste code	16 01 13* The Wast disposal c		sion between the user, the producer and the waste	
Disposal methods/information	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.			
Special precautions	Dispose in	accordance with all applicable regu	lations.	
SECTION 14: Transport in	formation	ı		
ADR				
14.1 14.6.: Not regulated as	s dangerous	goods.		

RID

14.1. - 14.6.: Not regulated as dangerous goods.

ADN

14.1. - 14.6.: Not regulated as dangerous goods.

ΙΑΤΑ

14.1. - 14.6.: Not regulated as dangerous goods.

IMDG

14.1. - 14.6.: Not regulated as dangerous goods.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Retained direct EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended Not listed.

Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended Not listed

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended Not listed

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended Not listed

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended Not listed

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA Not listed.

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorisation, as amended Not listed

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use, as amended - Conditions of restriction given for the associated entry number should be considered

2-(2-Methoxyethoxy)ethanol (CAS 111-77-3)

Tris[2-[2-(2-methoxyethoxy) ethoxy]ethyl] orthoborate (CAS 30989-05-0)

Other regulations

This product is classified and labelled in accordance with the retained CLP Regulation (EC) No 1272/2008, as amended for Great Britain.

This Safety Data Sheet is compiled in accordance with REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758.

New or expectant mothers should not work with this product if there is a risk due to exposure, in accordance with the Management of Health and Safety at Work Regulations 1999 [SI 1999/3242], as amended. Follow the requirements of the Control of Substances Hazardous to Health Regulations 2002 [SI 2002/2677], as amended, when using this material.

15.2. Chemical safety

No Chemical Safety Assessment has been carried out.

assessment

SECTION 16: Other information

List of abbreviations

ADN: European Agreement Concerning the International Carriage of Dangerous Goods by Inland Waterways. ADR: Agreement concerning the International Carriage of Dangerous Goods by Road. CAS: Chemical Abstract Service. CEN: European Committee for Standardization. DNEL: Derived No-Effect Level. EC50: Effective Concentration, 50%. IATA: International Air Transport Association. IMDG: International Maritime Dangerous Goods. IMO: International Maritime Organization. LC50: Lethal Concentration, 50%. LD50: Lethal Dose, 50%. NOEC: No observed effect concentration. PBT: Persistent, bioaccumulative and toxic. PNEC: Predicted No-Effect Concentration. RID: Regulations concerning the International Carriage of Dangerous Goods by Rail.

	TWA: Time Weighted Average. vPvB: Very persistent and very bioaccumulative.
References	HSDB® - Hazardous Substances Data Bank ECHA: European Chemical Agency. Registry of Toxic Effects of Chemical Substances (RTECS)
Information on evaluation method leading to the classification of mixture	The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.
Full text of any statements, which are not written out in full	
under sections 2 to 15	 H318 Causes serious eye damage. H319 Causes serious eye irritation. H360D May damage the unborn child. H361fd Suspected of damaging fertility. Suspected of damaging the unborn child.
This SDS contains revisions in the following section(s):	1, 2, 3, 4, 6, 7, 8, 9, 11, 12, 15, 16.
Training information	Follow training instructions when handling this material.
Further information	UFI: 64A0-204C-000V-49WJ UFI: DWKJ-348Q-W00U-9D1H
Disclaimer	The information provided on this data sheet was abstracted from supplier safety data sheets and standard references in occupational health and toxicology. Federal-Mogul makes no representation or warranty with respect to the information obtained from such references. The information is however, as of the date provided, true and accurate to the best of Federal-Mogul's knowledge, and should be used to make an independent determination of the methods to safeguard workers and the environment.